



Kit Revision Date: 23/09/2021

8330S SILVER CONDUCTIVE EPOXY ADHESIVE KIT

MG Chemicals Multipart Product Kit

This product is a kit made up of multiple parts. Each part is an independently packaged chemical component and has independent hazard assessments.

Kit Content

<i>Part</i>	<i>Product Name</i>	<i>Product Use</i>
A	8330S-A	Electrically conductive epoxy adhesive resin part for use with hardeners
B	8330S-B	Electrically conductive epoxy adhesive hardener part for use with resins

Safety Data Sheets for each part listed above follow this cover sheet.

Transportation Instruction

Before offering this product kit for transport, read Section 14 for all parts listed above.

8330S-A

(PART A)

Safety Data Sheet

Section 1: Identification



Product Identifier and Other Means of Identification

Product Identifier: 8330S-A**Other Means of Identification:** Silver Conductive Epoxy Adhesive**Related Part #** 8330S-21G, 8330S-50ML, 8330S-200ML

Recommended Use and Restriction on Use

Use: Electrically conductive epoxy adhesive resin part for use with hardeners**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA +1-800-340-0772 +1-905-331-1396**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number



For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8330S-A
(PART A)
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning
Eye Irritation		2	Warning
Skin Irritation		2	Warning
Hazardous to the Aquatic Environment	Chronic	1	Warning
			Exclamation
			Exclamation
			Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H317: May cause an allergic skin reaction H319: Causes serious eye irritation H315: Causes skin irritation
	H410: Very toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes and vapors.
P280	Wear protective gloves and eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

Section continued on the next page

Page **2** of **15**

Date: 18 January 2023 / Ver. 2.08

8330S-A
(PART A)
Continued...

Response	Precautionary Statements
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Argyria	Long term exposure to silver powder or compounds can lead to an irreversible blue-grey discoloration of the skin.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-22-4	silver	78%
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	20%
17557-23-2	neopentyl glycol diglycidyl ether	2%

8330S-A
(PART A)
Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	<i>redness, irritation, allergic dermatitis, rash</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, irritation</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF INHALED	P304 + P340
Immediate Symptoms	<i>Low toxicity—cough, irritation of the respiratory track, sore throat, asthma for pre-sensitized individuals</i>
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>low toxicity: abdominal discomfort, nausea, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use extinguishing media suitable for surrounding materials.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Inhalation of silver oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO,CO ₂), and toxic metal fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

8330S-A**(PART A)****Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing fumes or vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	No containment method required—this product is not readily flowable
Cleaning Methods	Collect liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Avoid breathing fumes and vapors. Avoid release to the environment. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.
Handling	Wear protective gloves/eye protection. Wash hands thoroughly after handling. Collect spillage.
Storage	Not available

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
silver (metal dust, mist) (metal) (Ag and its compounds) (metal, dust, fumes)	ACGIH	0.1 mg/m ³	Not established
	U.S.A. OSHA PEL	0.01 mg/m ³	Not established
	Canada AB	0.1 mg/m ³	Not established
	Canada BC	0.01 mg/m ³	0.03 mg/m ³
	Canada ON	0.1 mg/m ³	Not established
	Canada QC	0.1 mg/m ³	Not established

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation

Keep airborne concentrations below the occupational exposure limits (OEL).

The silver flakes are inextricably bound to the adhesive mixture; therefore they are not available as airborne hazards under normal use. Ensure adequate ventilation if the product is mechanically aerosolized.

Personal Protective Equipment

Eye protection

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Ensure that glasses have side shields for lateral protection.

Skin Protection

For likely contacts, use of protective butyl rubber, latex, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

8330S-A
(PART A)

Respiratory Protection If exposed to fumes or dust above the exposure limit, wear a suitable respirator meeting local/regional/national guidelines.

If the product is heated or the worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not available
Appearance	Silver grey, paste	Upper Flammability Limit	Not available
Odor	Slight	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	3.54
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point	Not available	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	127 °C [261 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not available	Viscosity @40 °C	>20.5 mm ² /s

a) The closed cup flash point values are based on the phenol, polymer with formaldehyde, glycidyl ether resin component.

8330S-A
(PART A)
Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with amines.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid high temperatures, open flames, and incompatible substances. Do not use in a way that aerosolizes the product.
Incompatibilities	Avoid strong oxidizing agents, strong acids, strong bases
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information
Summary of Effects and Symptoms by Routes of Exposure

Eyes	May cause redness and mild irritation.
Skin	May cause skin redness, mild irritation, dry skin, or allergic contact dermatitis.
Inhalation	May cause cough, respiratory irritation, sore throat, or asthma.
Ingestion	Low toxicity: It may cause abdominal discomfort, nausea, vomiting (see inhalation symptoms).
Chronic	Prolonged and repeated exposure may lead to skin sensitization. Prolonged and repeated ingestion or inhalation of silver may yield to an irreversible blue-grey discoloration of the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
silver	>5 g/kg Guinea Pig	>2 000 mg/kg Rabbit	>5.16 mg/L Rat 4 h (dust)
phenol, polymer with formaldehyde, glycidyl ether	Not available	Not available	Not available
neopentyl glycol diglycidyl ether	>2 000 mg/kg Rat ^{a)}	2 150 mg/kg Rabbit ^{a)}	Not available

Note: Toxicity data from the ECHA database were consulted. The data from supplier SDS were also consulted.

Section continued on the next page

8330S-A**(PART A)****Other Toxicological Effects**

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes severe eye irritation. Contains mechanically abrasive particles.
Sensitization (allergic reactions)	The epoxy resin components (CAS# 28064-14-4 and 17557-23-2) may cause skin sensitization in humans.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at $40 \text{ }^\circ\text{C}$.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains silver particles of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that is very toxic to the environment. While massive silver is insoluble in water, its powders is considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 1 (M = 10 for silver) of the EU.

In Europe, similar epoxy resin with CAS# 28064-14-4 is generally classified as chronic category 2 marine pollutant due to LC50 96 h of $>1 \text{ mg/L}$ but $\leq 10 \text{ mg/L}$.

Based on available data, neopentyl glycol diglycidyl ether is not classified as environmental hazard according to GHS criteria.

Section continued on the next page

8330S-A**(PART A)****Acute Ecotoxicity**

Category 1

Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

8330S-A

(PART A)

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 5 kg
8330S-15G, 8330S-50ML, 8330S-200ML

NOT REGULATED in TDG
per Special Provisions 99

Sizes 5 kg and under

NOT REGULATED in 49 CFR
per exception 171.4 (c)(2)

Sizes over 5 kg
FOR REFERENCE ONLY

UN number: UN3077
Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, SOLID,
N.O.S. (silver flakes <1 mm)

Class: 9
Packing Group: III
Marine Pollutant: Yes

Special Provision 99 (2): These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions: Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Section continued on the next page

8330S-A**(PART A)****Air****Refer to ICAO-IATA regulations.**

Sizes 5 kg and under
8330S-15G, 8330S-50ML, 8330S-200ML

NOT REGULATED

On air waybill, write:
"Not Restricted, as per Special Provisions A197"

Sizes over 5 kg
FOR REFERENCE ONLY

UN number: UN3077

Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(silver particles <1 mm, phenol, polymer with
formaldehyde, glycidyl ether)

Class: 9

Packing Group: III

Marine Pollutant: Yes

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea**Refer to IMDG regulations.**

Sizes 5 kg and under
8330S-15G, 8330S-50ML, 8330S-200ML

NOT REGULATED

per 2.10.2.7

Sizes over 5 kg
FOR REFERENCE ONLY

UN number: UN3077

Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(silver particles <1 mm, phenol, polymer
with formaldehyde, glycidyl ether)

Class: 9

Packing Group: III

Marine Pollutant: Yes

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

8330S-A**(PART A)****Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA**Other Classifications****HMIS® RATING**

HEALTH:	*	2
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains silver (CAS# 7440-22-4; reportable quantity = 1 000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

Section continued on the next page

8330S-A**(PART A)**

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemical's Regulatory Department

Date of Review 19 January 2023

Supersedes 09 March 2020

Reason for Changes: Update to to contact information.

Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

Section continued on the next page

8330S-A**(PART A)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.

8330S-B

(PART B)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8330S-B**Other Means of Identification:** Silver Conductive Epoxy Adhesive**Related Part #** 8330S-21G, 8330S-50ML, 8330S-200ML

Recommended Use and Restriction on Use

Use: Silver filled electrically conductive adhesive epoxy hardener for use with resins**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA**☎** +1-800-340-0772**☎** +1-905-331-1396**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number




For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8330S-B
(PART B)
Section 2: Hazard(s) Identification
Classification of the Chemical Material
GHS Categories

Criteria		Category	Signal Word	Pictograms
Eye Damage		1	Danger	Corrosion
Sensitization	Skin	1	Warning	Exclamation
Skin Irritant		2	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	1	Warning	Environment
Hazardous to the Aquatic Environment	Acute	1	Warning	Environment

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H318: Causes serious eye damage
	H317: May cause an allergic skin reaction H315: Causes skin irritation
	H400: Very toxic to aquatic life H410: Very toxic to aquatic life with long lasting effects

Section continued on the next page

8330S-B
(PART B)
Continued ...

Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes and vapors.
P280	Wear protective gloves and eye protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P305 + P351 + P338, P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P302 + P352, P362 + P364	IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P391	Collect spillage.
Disposal	Precautionary Statements
P501	Dispose of contents and container in accordance to local, regional, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Argyria	Long term ingestion or inhalation of silver can lead to an irreversible blue-grey discoloration of the skin.	None	None

8330S-B
(PART B)
Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
7440-22-4	silver	76%
68541-13-9	9,12-octadecadienoic acid-based polyamidoamine	12%
68082-29-1	fatty acid-polyethylamine polymer	8%
4246-51-9	3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine	2%
112-57-2	tetraethylenepentamine	0.5%
112-24-3	triethylenetetramine	0.01%

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	<i>redness, severe irritation, pain, burns</i>
Response	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
IF ON SKIN	P302 + P352, P333 + P313, P362 + P364
Immediate Symptoms	<i>redness, severe irritation, rash (allergic contact dermatitis)</i>
Response	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	<i>low toxicity: cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>low toxicity: no symptoms known or expected</i>
Response	Rinse mouth. Do not induce vomiting.

Section continued on the next page

8330S-B**(PART B)****Advice to Physicians**

In case of exposure to nitrogen oxides (NO_x) combustion products or triethylenetetramine vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use extinguishing media suitable for surrounding materials.
Specific Hazards	<p>Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces.</p> <p>Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.</p> <p>Toxic for aquatic environment: Prevent fire-fighting wash from entering waterway or sewer system.</p>
Combustion Products	Produces carbon oxides (CO, CO ₂), ammonia, nitric acid, nitrogen oxides (NO _x), and silver metal fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Avoid breathing the fumes or vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	None required—this product is not readily flowable.
Cleaning Methods	<p>Collect spill in a sealable container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Use soap and water to remove the last traces of residue.</p> <p>RECOMMENDATION: Use a plastic, stainless steel, or carbon steel container. Avoid containers with copper, aluminum, zinc, or galvanized surfaces since the waste material can slowly oxidize them.</p>
Disposal Methods	Dispose spill waste according to Section 13.

8330S-B
(PART B)
Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Avoid breathing fumes or vapors or contact with skin or eyes.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Handling

Wear protective gloves and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Collect spillage.

Storage

Keep away from acids and other incompatible substances.

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
silver (metal dust, mist) (metal) (Ag and its compounds) (metal, dust, fumes)	ACGIH	0.1 mg/m ³	Not established
	U.S.A. OSHA PEL	0.01 mg/m ³	Not established
	Canada AB	0.1 mg/m ³	Not established
	Canada BC	0.01 mg/m ³	0.03 mg/m ³
	Canada ON	0.1 mg/m ³	Not established
	Canada QC	0.1 mg/m ³	Not established
triethylenetetramine	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	1 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	0.5 ppm (Skin)	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h. Skin—can be absorbed through the skin.

Section continued on the next page

8330S-B**(PART B)****Engineering Controls****Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Due to low vapor pressure of the product, general ventilation should be adequate for normal use. If the product is heated at high temperatures or worker is allergic, use local ventilation and consider using a full mask with organic vapor cartridges.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands with water and soap after use.

8330S-B
(PART B)
Section 9: Physical and Chemical Properties

Physical State	Solid	Lower Flammability Limit	Not available
Appearance	Silver grey, paste	Upper Flammability Limit	Not available
Odor	Amine-like	Vapor Pressure @20 °C^{b)}	<0.48 hPa [<3.6 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	2.83
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point^{a)}	>221 °C [>430 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point^{a)}	>93 °C [>200 °F]	Auto-ignition Temperature	321 °C [610]
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non Flammable	Viscosity @25 °C	Not available

a) The boiling point and closed cup flash point values are based on the lowest value component: 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine.

b) Based on highest vapor pressure component

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with ketones and epoxides. May react violently with peroxides.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid excessive heat and incompatible substances.
Incompatibilities	Strong oxidizing agents, strong acids, peroxides
Polymerization	Will not occur
Decomposition	Doesn't decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	May causes redness, severe eye irritation, pain, or corrosive eye damage.
Skin	May cause redness, serious skin irritation, allergic contact dermatitis, and chemical burns. Triethylenetetramine can be absorbed through skin leading to toxic effects. When heated, hot triethylenetetramine vapors may also result in itching of the face with skin redness (erythema) and swelling (edema).
Inhalation	Low toxicity: inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract) and coughing.
Ingestion	Low toxicity: no symptoms known or expected.
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization. Prolonged and repeated ingestion or inhalation of silver may yield to an irreversible blue-grey discoloration of the skin.

Section continued on the next page

8330S-B
(PART B)
Lethal Exposure Concentrations

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
silver	>2 000 mg/kg Rat	>2 000 mg/kg Rabbit	>5.16 mg/L Rat 4 h (dust)
9,12-octadecadienoic acid-based polyamidoamine	Not available	Not available	Not available
fatty acid-polyethylamine polymer	>2 000 mg/kg Rat	>2 000 mg/kg Rat	Not available
3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine	3 160 mg/kg Rat	2 510 mg/kg Rat	Not available
tetraethylenepentamine	3 990 mg/kg Rat	660 mg/kg Rabbit	Not available
triethylenetetramine	2 500 mg/kg Rat	805 mg/kg Rabbit	Not available
Mixture ATE	2 577 mg/kg	2 517 mg/kg	Not available

Note: Toxicity data from the ECHA database were consulted. The data from supplier SDS were also consulted.

a) Supplier SDS

Other Toxicological Effects
Skin corrosion/irritation

The 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine; tetraethylenepentamine; and triethylenetetramine are category 1 skin corrosive substances.

Serious eye damage/irritation

Fatty acid-polyethylamine polymer; 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine; tetraethylenepentamine; and triethylenetetramine cause severe eye damage. Contains mechanically abrasive particles.

Sensitization

(allergic reactions)

Fatty acid-polyethylamine polymer; 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine; tetraethylenepentamine; and triethylenetetramine may cause skin sensitization according to animal studies.

Section continued on the next page

8330S-B**(PART B)****Carcinogenicity**

(risk of cancer)

None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP

Mutagenicity

(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity

(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity

(risk of fetus malformation)

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met. See the hazard not otherwise specified danger of argyria in section 2.

Aspiration hazardBased on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains silver particles of less than a 1 mm but more than 100 nm (larger than nanoparticles), which release ionic silver levels that is very toxic to the environment. While massive silver is insoluble in water, its powders is considered sufficiently soluble to give rise to an ecological hazard by EU regulators. The classification that follows takes into account to chronic aqueous toxicity of category 1 (M = 10 for silver) of the EU.

The fatty acid-polyethylamine polymer and tetraethylenepentamine are classified as a chronic category 2 environmental toxicant.

The 3,3'-(oxybis(2,1-ethane-diyloxy))bis-1-propanamine is classified as a chronic category 3 environmental toxicant.

The 9,12-octadecadienoic acid-based polyamidoamine is not classified as an ecotoxic substance.

Literature values for the triethylenetetramine (CAS# 112-24-3) suggest an acute category 3 aquatic toxicity (LC50, IC50, and EC50 values of >100 mg/L for fish and between 10 and 100 mg/L for algae).

Acute Ecotoxicity

Category 1

Very toxic to aquatic life

Chronic Ecotoxicity

Category 1

Very toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Regulated Volatile Organic Compounds (VOC) content according to the US (EPA) and Canadian (CEPA) authorities.

VOC = 24% [745 g/L]

8330S-B

(PART B)

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 5 kg
8330S-15G, 8330S-50ML, 8330S-200ML
NOT REGULATED in TDG
per Special Provisions 99

Sizes 5 kg and under
NOT REGULATED in 49 CFR
per exception 171.4 (c)(2)

Sizes over 5 kg
FOR REFERENCE ONLY
UN number: UN3077
Shipping Name: ENVIRONMENTALLY
HAZARDOUS SUBSTANCE, SOLID,
N.O.S. (silver particles <1 mm)
Class: 9
Packing Group: III
Marine Pollutant: Yes

Special Provision 99 (2):

These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

171.4 (c) Exceptions:

(2) Single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements of this subchapter provided the packagings meet the general requirements in §§ 173.24 and 173.24a. This exception does not apply to marine pollutants that are a hazardous waste or a hazardous substance. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this subchapter relevant to any additional hazards continue to apply.

Section continued on the next page

8330S-B

(PART B)

Air

Refer to ICAO-IATA regulations.

Sizes 5 kg and under
8330S-15G, 8330S-50ML, 8330S-200ML
NOT REGULATED
On air waybill, write:
"Not Restricted, as per Special Provisions A197"

Sizes over 5 kg
FOR REFERENCE ONLY
UN number: UN3077
Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (silver particles <1 mm, phenol, polymer with formaldehyde, glycidyl ether)
Class: 9
Packing Group: III
Marine Pollutant: Yes

Special Provision A197: These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Sea

Refer to IMDG regulations.

Sizes 5 kg and under
8330S-15G, 8330S-50ML, 8330S-200ML
NOT REGULATED
per 2.10.2.7

Sizes over 5 kg
FOR REFERENCE ONLY
UN number: UN3077
Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (silver particles <1 mm, phenol, polymer with formaldehyde, glycidyl ether)
Class: 9
Packing Group: III
Marine Pollutant: Yes

2.10.2.7: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information
Canada
Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)


All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

USA
Other Classifications
HMIS® RATING

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES


Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains silver (CAS# 7440-22-4), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Section continued on the next page

8330S-B**(PART B)****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemical's Regulatory Department

Date of Revision 19 January 2023

Supersedes 19 November 2022

Reason for Changes: Composition update

Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

8330S-B**(PART B)**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.