

422C

(AEROSOL)

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 422C**Other Means of Identification:** Silicone Conformal Coating**Related Part #** 422C-340G, 422C-445ML

### Recommended Use and Restriction on Use

**Use:** Conformal coating**Uses Advised Against:** Not applicable

### Details of Manufacturer or Importer

#### Manufacturer

MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA

MG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA

**☎** +1-800-340-0772**Fax** +1-800-340-0773**E-mail** [support@mgchemicals.com](mailto:support@mgchemicals.com)**Web** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**Fax** +1-905-331-2682**E-mail** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-mail:** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)




**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**422C**
**(AEROSOL)**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Flammable Aerosol	2	Warning	Flame
Gas Under Pressure	Liquefied Gas	Warning	Gas cylinder
Eye Irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>Warning</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H223: Flammable Aerosol
	H280: Contains gas under pressure; may explode if heated
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness

*Section continued on the next page*

**422C**
**(AEROSOL)**
*Continued...*

<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not piece or burn, even after use.
P261	Avoid breathing mist, vapors, and spray.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye protection.
<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or doctor if you feel unwell.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403 + P233	Store in a well-ventilated place.
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of container in accordance to local, regional, national, and international regulations.

**Hazards Not Otherwise Classified**

<b>Other Criteria</b>	<b>Hazard Statements/Precautionary Statement</b>	<b>Signal Word</b>	<b>Pictograms</b>
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

**422C**
**(AEROSOL)**
**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
67-64-1	acetone	32%
115-10-6	dimethyl ether	30%
123-86-4	n-butyl acetate	18%
2530-83-8	gamma-glycidoxypropyltrimethoxysilane	2%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P337 + P313
<b>Immediate Symptoms</b>	<i>redness, severe irritation, pain, blurred vision</i>
<b>Response</b>	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>IF INHALED</b>	P304 + P340, P312
<b>Immediate Symptoms</b>	<i>cough, sore throat, headache, dizziness, drowsiness, shortness of breath</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
<b>IF ON SKIN</b>	P302 + P352
<b>Immediate Symptoms</b>	<i>low toxicity: dry skin, redness</i>
<b>Response</b>	Wash with plenty of water.
<b>IF SWALLOWED</b>	P301 + P330, P331
<b>Immediate Symptoms</b>	<i>low toxicity: abdominal pain, diarrhea, nausea, vomiting</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting.

422C

**(AEROSOL)****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.  Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].  The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), silicon oxides (SO <sub>2</sub> ), formaldehyde and other toxic fumes.
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Avoid breathing the mist, spray, and vapors. Remove or keep away all sources of ignition or extreme heat.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.  <b>RECOMMENDATION:</b> Use a grounded stainless steel or carbon steel container.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**422C**
**(AEROSOL)**
**Section 7: Handling and Storage**
**Prevention**

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not piece or burn, even after use.

Avoid breathing mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

**Handling**

Wash hand thoroughly after handling.

Wear eye protection and face protection.

**Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

Store in a well-ventilated place.

Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
acetone	ACGIH	500 ppm	750 ppm
	U.S.A. OSHA PEL	1 000 ppm	Not established
	Canada AB	500 ppm	750 ppm
	Canada BC	250 ppm	500 ppm
	Canada ON	500 ppm	750 ppm
	Canada QC	750 ppm	1 000 ppm
dimethyl ether	ACGIH	Not established	Not established
	U.S.A. WEEL	1 000 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	1 000 ppm	Not established
	Canada ON	Not established	Not established
	Canada QC	Not established	Not established

*Section continued on the next page*

**422C**
**(AEROSOL)**
*Continued...*

Chemical Name	Country/Province	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
n-butyl acetate	ACGIH	150 ppm	200 ppm
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	Not established
	Canada ON	150 ppm	200 ppm
	Canada QC	150 ppm	200 ppm

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

### Engineering Controls

**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

### Personal Protective Equipment

**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

*Section continued on the next page*

**422C**
**(AEROSOL)**
**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid, aerosol format	<b>Lower Flammability Limit</b> <sup>b)</sup>	2%
<b>Appearance</b>	Clear	<b>Upper Flammability Limit</b> <sup>b)</sup>	9.4%
<b>Odor</b>	Ester-like	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	<2.01 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	0.88
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Insoluble
<b>Initial Boiling Point</b> <sup>a)</sup>	56 °C [132 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	-17 °C [1.4 °F]	<b>Auto-ignition Temperature</b> <sup>c)</sup>	≥200 °C [≥392 °F]
<b>Evaporation Rate</b>	<1 (ButAc = 1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Flammable	<b>Viscosity @25 °C</b>	Not available

a) Values based on acetone

b) Values based on Raoult's Law

c) Values based on dimethyl ether, which is the component with the lowest auto-ignition value



**422C**
**(AEROSOL)**
**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures.
<b>Conditions to Avoid</b>	Avoid direct sunlight, temperatures above 50 °C [122 °F], open flames, sparks, and incompatible substances.
<b>Incompatibilities</b>	Strong oxidizing agents, strong bases, strong reducing agents, strong acids
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	Causes redness, severed irritation, pain, and blurred vision.
<b>Skin</b>	May cause dry skin and redness.
<b>Inhalation</b>	May cause dizziness, drowsiness, coughing, sore throat, headache, and nausea.
<b>Ingestion</b>	Low toxicity: May cause abdominal pain, diarrhea, nausea, and vomiting.
<b>Chronic</b>	Prolonged or repeated exposure may cause skin may cause skin dryness and cracking.

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
acetone	5 800 mg/kg Rat	20 mL/kg Rabbit <sup>a)</sup>	16 000 ppm 4 h Rat <sup>a)</sup>
dimethyl ether	Not available	Not available	308 g/m <sup>3</sup> Rat
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat

*Section continued on the next page*

**422C**
**(AEROSOL)**
*Continued ...*

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
gamma-glycidoxypropyltrimethoxysilane	Not available	Not available	Not available

*Note:* Toxicity data from the ECHA databases were consulted. The data from supplier SDSs were also consulted.

### Other Toxicological Effects

<b>Skin Corrosion/Irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious Eye Damage/Irritation</b>	Silane, trimethoxy[3-(oxiranylmethoxy) propyl]- can cause eye damage.
<b>Sensitization</b> (allergic reactions)	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-Single Exposure</b>	The ingredients acetone and n-butyl acetate can affect the central nervous system by inhalation causing drowsiness or dizziness.
<b>STOT-Repeated Exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration Hazard</b>	Based on available data, the classification criteria are not met. There are no cat 1 substances, and the kinematic viscosity is >20.5 mm <sup>2</sup> /s at 40 °C.

422C

**(AEROSOL)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The ingredients acetone, n-butyl acetate, dimethyl ether, and silane, trimethoxy[3-(oxiranylmethoxy)propyl] are not classified as an environmental hazard according to GHS criteria.

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds.

**Other Effects**

Volatile Organic Compounds (VOC) = 49% [439 g/L]

Product-weighted Maximal Incremental Reactivity (MIR) = 0.56 O<sub>3</sub>/g product

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

422C

(AEROSOL)

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

**Limited Quantity**



**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



**UN number:** UN1950  
**Shipping Name:** AEROSOLS, flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No

**Sea**

**Refer to IMDG regulations.**

**Limited Quantity**



**UN number:** UN1950  
**Shipping Name:** AEROSOLS, flammable  
**Class:** 2.1  
**Packing Group:** Not applicable  
**Marine Pollutant:** No

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**422C**
**(AEROSOL)**
**Section 15: Regulatory Information**
**Canada**
**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

**USA**
**Other Classifications**
**HMIS® RATING**

<b>HEALTH:</b>	<b>* 2</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains acetone (CAS# 67-64-1) and n-butyl acetate (CAS# 123-86-4), which are subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

*Section continued on the next page*

**422C****(AEROSOL)**

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any substances known to be listed in California.

## Europe

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

## Section 16: Other Information

**SDS Prepared by** Regulatory Department

**Date of Creation** 03 October 2022

**Supersedes** 22 March 2021

**Reason for Changes:** New part number.

### Reference

1) ACGIH 2022 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2022).

*Section continued on the next page*

**422C****(AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content
Wt	Weight

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Telephone: +1-905-331-1396

<b>Mailing Addresses</b>	Manufacturing & Support	Head Office
	1210 Corporate Drive	9347-193rd Street
	Burlington, Ontario, Canada	Surrey, British Columbia, Canada
	L7L 5R6	V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. M.G. Chemicals, Ltd. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.