



Safety Data Sheet

according to WHMIS 2025 and HCS 2024

1 Identification

Product identifier

Trade name: 835

Other Means of Identification: Rosin Flux

Related Part Number: 835-Liquid, 835-100ML, 835-100MLCA, 835-1L, 835-4L, 835-20L

Application of the substance / the mixture Flux

Uses advised against Not available

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 800-340-0772
+(1) 905-331-1396
info@mgchemicals.com

Distributor:

Mouser Electronics
1000 North Main Street
Mansfield, TX 76063
USA
+(1) 817-804-3800
Masline
511 Clinton Ave S
Rochester, New York 14620
United States
+(1) 586-546-5373

Information department: sds@mgchemicals.com

Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA-Call 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

Classification of the substance or mixture

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category 3

H335 May cause respiratory irritation.

3

Specific target organ toxicity (single exposure) – Category 3

H336 May cause drowsiness or dizziness.

3

(Contd. on page 2)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Trade name: 835

(Contd. of page 1)

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Rosin, polymerized
butanol
ethanol

· Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

· Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof lighting equipment.
P243 Take action to prevent static discharges.
P261 Avoid breathing fumes and vapors.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, and eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

· Other hazards

Warning! Oxidized rosin-based solder fumes are capable of inciting occupational asthma in some pre-sensitized individuals.

(Contd. on page 3)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

Repeated exposure may cause skin dryness or cracking.

(Contd. of page 2)

3 Composition/Information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|--------------------|--------------|
| 65997-05-9 | Rosin, polymerized | 45-51% w/w * |
| 78-92-2 | butanol | 25-28% w/w * |
| 64-17-5 | ethanol | 23-26% w/w * |

* Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

- **After skin contact:**

Take off immediately all contaminated clothing.

Wash with plenty of soap and water.

- **After eye contact:**

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

- **After swallowing:**

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

- **Most important symptoms and effects, both acute and delayed**

See section 11 for additional information.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Trade name: 835

(Contd. of page 3)

· **Special hazards arising from the substance or mixture**

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

Prevent fire-fighting wash from entering waterway or sewer system.

· **Hazardous combustion products:**

Carbon Oxides (COx)
by-products of pyrolysis of abietic resin acids

· **Advice for firefighters**

· **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Avoid breathing the fumes or vapors.
Remove or keep away all sources of extreme heat or open flames.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**

Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Avoid breathing mist, spray, or vapors.
Use only outdoors or in a well-ventilated area.
For frequent or prolonged soldering processes, use of a local exhaust system to avoid exposure to thermal decomposition products. For example, use fume cabinet, a hood on a flexible arm, or tip-mounted fume extraction system on the soldering iron.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.

(Contd. on page 5)

Safety Data Sheet
according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 4)

Ground and bond container and receiving equipment.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Keep in a dry and clean area, away from incompatible substances

· **Information about storage in one common storage facility:** Not required

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store locked up.

· **Specific end use(s)** See section 1.2

*** 8 Exposure controls/ Personal protection**

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

| 78-92-2 butanol | |
|-----------------|---|
| EL (Canada) | TWA: 100 ppm |
| EV (Canada) | STEL: 150 ppm TWA: 100 ppm |
| PEL (USA) | TWA: 450 mg/m ³ , 150 ppm |
| REL (USA) | STEL: 455 mg/m ³ , 150 ppm TWA: 305 mg/m ³ , 100 ppm |
| TLV (USA) | TWA: 303 mg/m ³ , 100 ppm |
| 64-17-5 ethanol | |
| EL (Canada) | STEL: 1000 ppm |
| EV (Canada) | TWA: 1,900 mg/m ³ , 1,000 ppm |
| PEL (USA) | TWA: 1900 mg/m ³ , 1000 ppm |
| REL (USA) | TWA: 1900 mg/m ³ , 1000 ppm |
| TLV (USA) | STEL: 1880 mg/m ³ , 1000 ppm A3 |

· **Additional information:**

The lists that were valid during the creation were used as basis.

Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **Exposure controls**

· **Appropriate engineering controls** Keep airborne concentrations below exposure limits.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 6)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Trade name: 835

(Contd. of page 5)

· **Breathing equipment:**

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus. Advice should be sought from respiratory protection specialists.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses or tightly sealed goggles: EN 166

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

| | |
|---------------------------------------|--------------------|
| · Physical state | Liquid |
| · Form: | Viscous |
| · Color: | Amber colored |
| · Odor: | Alcohol-like |
| · Odor threshold: | Not determined |
| · Melting point/Melting range: | Undetermined |
| · Boiling point/Boiling range: | ≥78 °C (≥172.4 °F) |
| · Flammability: | Highly flammable. |
| · Explosion limits: | |
| · Lower: | 3 Vol % |
| · Upper: | 16 Vol % |

(Contd. on page 7)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Trade name: 835

(Contd. of page 6)

| | |
|--|--|
| · Flash point: | 13 °C (55.4 °F) |
| · Auto igniting: | 390 °C (734 °F) |
| · Decomposition temperature: | Not determined |
| · Viscosity: | |
| · Kinematic: | Not determined |
| · Dynamic: | Not determined |
| · Solubility in / Miscibility with | |
| · Water: | Partly miscible. |
| · Partition coefficient (n-octanol/water): | Not determined |
| · Vapor pressure at 20 °C (68 °F): | 42 hPa (31.5 mm Hg) |
| · Relative density at 25 °C (77 °F): | 0.93 |
| · Vapor density (air=1): | >1.5 |
| · Particle characteristics | Not applicable |
| · Other information | |
| · Important information on protection of health and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Organic solvents: | 48–54 % |
| · VOC content: | 48–54 % |
| · Solids content: | 0.0 % |
| · Evaporation rate | 1.9 (ButAc=1) |

10 Stability and reactivity

· **Reactivity**

Polymerized rosin is oxidation resistant but may contains residual unmodified resin acids that can be auto-oxidize in contact with air and sunlight. Some slow auto-oxidation can also occur after long storage durations. The oxidation by-products may cause sensitization.

· **Chemical stability** Chemically stable at normal temperatures and pressures.

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.

· **Incompatible materials:**

Strong oxidizing agents
Strong acids

· **Hazardous decomposition products:**

Hazardous combustion products: see section 5.

Thermal degradation produces oxidized rosin by-products that are known skin and respiratory sensitizers.

(Contd. on page 8)

Safety Data Sheet
according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 7)
 At soldering temperatures, it may generate pyrolysis products that include acetone, aliphatic aldehydes, methyl alcohol, methane, ethane, various abietic acids (the major components of rosin), CO and CO₂.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

| | | |
|------------------------|----------|-------------------|
| 78-92-2 butanol | | |
| Oral | LD50 | 6,480 mg/kg (rat) |
| 64-17-5 ethanol | | |
| Oral | LD50 | 7,060 mg/kg (rat) |
| Inhalative | LC50/4 h | 20,000 mg/L (rat) |

· **Primary irritant effect:**

· **on the eye:** Irritating effect.

· **Summary of effects and symptoms by route of exposure**

· **Eyes:**

watering
 eye prickling
 swelling
 redness, serious irritation

· **Skin:**

redness
 dry skin

· **Inhalation:**

irritation of the respiratory tract
 cough
 dizziness or drowsiness
 sore throat

· **Swallowed:**

irritation to the mouth, throat, esophagus, and stomach
 see inhalation symptoms

· **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

Repeated or prolonged inhalation exposure to solder pyrolysis by-products may cause certain sensitive individuals to develop asthma and eczema symptoms.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

· **Carcinogenic categories**

| | |
|---|---|
| · IARC (International Agency for Research on Cancer) | |
| 64-17-5 ethanol | 1 |

(Contd. on page 9)

Safety Data Sheet
according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 8)

| |
|--|
| · NTP (National Toxicology Program) |
| None of the ingredients is listed. |

12 Ecological information

· **Toxicity**

| |
|--|
| · Aquatic toxicity: |
| 78-92-2 butanol |
| EC50/ 48 h 2,300 mg/L (daphnia) |
| LC50 96h 3,670 mg/L (minnow) |
| 64-17-5 ethanol |
| LC50 >1,000 mg/L (fish) Biodegradable |

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable
 - **vPvB:** Not applicable
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** This material and its container must be disposed of as hazardous waste.
- **Uncleaned packagings:**
 - **Recommendation:**
Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.
 - **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

| | |
|------------------------------|--------|
| · UN-Number | UN1987 |
| · DOT/TDG, IMDG, IATA | |

(Contd. on page 10)

Safety Data Sheet
according to WHMIS 2025 and HCS 2024




Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 9)

| | |
|---|---|
| <ul style="list-style-type: none"> · UN proper shipping name · DOT/TDG, IATA · IMDG | <p>Alcohols, n.o.s. (ethanol, butanol) ALCOHOLS, N.O.S. (ethanol, butanol)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT/TDG (Transport dangerous goods): | |
|  <ul style="list-style-type: none"> · Class · Label | <p>3 Flammable liquids 3</p> |
| <ul style="list-style-type: none"> · IMDG, IATA | |
|  <ul style="list-style-type: none"> · Class · Label | <p>3 Flammable liquids 3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT/TDG, IMDG, IATA | <p>II</p> |
| <ul style="list-style-type: none"> · Environmental hazards: | <p>Not applicable</p> |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <p>Not applicable</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
|  Limited Quantity 835-100ML, 835-100MLCA, 835-1L | |
| <ul style="list-style-type: none"> · DOT/TDG · Quantity limitations | <p>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</p> |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</p> |
| <ul style="list-style-type: none"> · Special precautions for user | <p>Not applicable</p> |

(Contd. on page 11)



Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 10)

| | |
|---|--|
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E,S-D |
| · Stowage Category | B |
| · UN "Model Regulation": | UN 1987 ALCOHOLS, N.O.S. (ETHANOL, BUTANOL), 3, II |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· OSHA Hazard Communication Standard (29 CFR Part 1900)

The safety data sheet and label comply with HCS 2024.

· Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2022.

· Sara

| |
|---|
| · Section 355 (extremely hazardous substances): |
| None of the ingredients is listed. |

| |
|---|
| · Section 313 (Specific toxic chemical listings): |
| 78-92-2 butanol |

| |
|--|
| · TSCA (Toxic Substances Control Act): |
| All components have the value ACTIVE. |

| |
|------------------------------------|
| · Hazardous Air Pollutants |
| None of the ingredients is listed. |

· Proposition 65

| |
|------------------------------------|
| · Chemicals known to cause cancer: |
| None of the ingredients is listed. |

| |
|---|
| · Chemicals known to cause reproductive toxicity for females: |
| None of the ingredients is listed. |

| |
|---|
| · Chemicals known to cause reproductive toxicity for males: |
| None of the ingredients is listed. |

| |
|--|
| · Chemicals known to cause developmental toxicity: |
| 64-17-5 ethanol |

· Carcinogenic categories

| |
|-------------------------------|
| · TLV (Threshold Limit Value) |
| 64-17-5 ethanol |
| A3 |

| |
|--|
| · NIOSH-Ca (National Institute for Occupational Safety and Health) |
| None of the ingredients is listed. |

(Contd. on page 12)

Safety Data Sheet

according to WHMIS 2025 and HCS 2024

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 11)

· Canadian substance listings:

| | |
|---|---------|
| · Canadian Domestic Substances List (DSL) | |
| All ingredients are listed. | |
| · Canadian Non-Domestic Substances List (NDSL) | |
| None of the ingredients is listed. | |
| · Canadian Ingredient Disclosure list (limit 0.1%) | |
| 64-17-5 | ethanol |
| · Canadian Ingredient Disclosure list (limit 1%) | |
| 78-92-2 | butanol |

· HMIS-ratings (scale 0 - 4)

Health = * 2
Fire = 3
Reactivity = 0

· Europe**· RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

· Per- and polyfluoroalkyl substances (PFAS)

None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Regulatory department

· **Contact:** sds@mgchemicals.com

· **Date of previous version** 10/01/2024

· **Version number of previous version:** 8.02

· **Date of preparation** 05/15/2026

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

(Contd. on page 13)



Safety Data Sheet
according to WHMIS 2025 and HCS 2024

Page 13/13

Date of issue 05/15/2026

Version number 8.03

Revision: 05/15/2026

Trade name: 835

(Contd. of page 12)

NIOSH: National Institute for Occupational Safety

· * **Data compared to the previous version altered.**

— CA —