

ETHYL ACETATE

9620-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Ethyl Acetate**SDS Code:** 9620-Liquid**Related Part #** 9620-945ML, 9620-3.78L

Recommended Use and Restriction on Use

Use: Solvent**Uses Advised Against:** Not applicable

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)



For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

ETHYL ACETATE
9620-LIQUID
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness and dizziness
Prevention	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist, vapors or spray.
P271	Use only outdoors or in well-ventilated area.
P233	Keep container tightly closed.
P264	Wash hands thoroughly after handling.

ETHYL ACETATE
9620-LIQUID
Section continued on the next page
Continued...

Prevention	Precautionary Statements
P280	Wear protective gloves, protective clothing, and eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340, P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents and container in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
141-78-6	ethyl acetate	100%

ETHYL ACETATE**9620-LIQUID****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF ON SKIN (or hair)	P303 + P361 + P353
Immediate Symptoms	<i>dry skin</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, redness, pain</i>
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>cough, dizziness, drowsiness, headache, nausea, sore throat, weakness, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
IF SWALLOWED	P301 + P330, P331
Immediate Symptoms	<i>See inhalation symptoms</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

ETHYL ACETATE**9620-LIQUID****Section 6: Accidental Release Measures**

Personal Protection	See personal protection equipment in Section 8.
Precautions for Response	Avoid breathing the mist, spray, or vapors. Remove or keep away all sources of ignition or extreme heat.
Environmental Precautions	Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect the liquid in a sealable, chemical-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Use soap and water to remove the last traces of residue. RECOMMENDATION: Use a grounded stainless steel or carbon steel container.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No Smoking. Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion-proof equipment. Avoid breathing vapors, mist, or spray. Use only outdoors or in a well-ventilated area.
Handling	Wear protective gloves and protective clothing or eye protection. Wash hands thoroughly after handling.
Storage	Store in a well-ventilated area. Keep cool. Store locked up.

ETHYL ACETATE
9620-LIQUID
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
ethyl acetate	ACGIH	400 ppm	Not established
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	400 ppm	Not established
	Canada BC	150 ppm	Not established
	Canada ON	400 ppm	Not established
	Canada QC	400 ppm	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection For likely contacts, use of protective butyl rubber, fluorinated rubber, or other chemically resistant gloves.

For incidental contacts, use neoprene, natural latex rubber, or other chemically resistant gloves.

Section continued on the next page

ETHYL ACETATE
9620-LIQUID
Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	2.2%
Appearance	Colorless to Slight Yellow	Upper Flammability Limit	11.5%
Odor	Ester, sweet	Vapor Pressure @20 °C	99 hPa [74 mmHg]
Odor Threshold	3.9 ppm	Vapor Density	3.0 (Air = 1)
pH	Not available	Relative Density @25 °C	0.902
Freezing/Melting Point	-83 °C [-117 °F]	Solubility in Water	83.1 g/L Very soluble
Initial Boiling Point	78 °C [172 °F]	Partition Coefficient n-octanol/water	0.73
Flash Point ^{a)}	-4 °C [25 °F]	Auto-ignition Temperature	485 °C [905 °F]
Evaporation Rate	4.1 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly flammable	Viscosity @40 °C	<20.5 mm ² /s

a) Closed cup value

ETHYL ACETATE**9620-LIQUID****Section 10: Stability and Reactivity**

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures.
Conditions to Avoid	Avoid flames, sparks, other ignition sources and incompatible substances.
Incompatibilities	Strong oxidizing agents
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Causes redness, serious eye irritation, and pain.
Skin	May cause dry skin.
Inhalation	May cause cough, sore throat, nausea, headache, and drowsiness, dizziness. Severe overexposure may lead to unconsciousness.
Ingestion	May cause nausea, weakness, headaches (see also inhalation symptoms).
Chronic	Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
ethyl acetate	5 620 mg/kg Rat	>20 000 mg/kg Rabbit	45 g/m ³ 2 h Mouse

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDS were also consulted.

Section continued on the next page

ETHYL ACETATE**9620-LIQUID****Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/irritation	Based on available data, ethyl acetate is slight eye irritant. However, harmonizing with Annex VI classification as severe eye irritant.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Based on available data, the classification criteria are not met.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Ethyl acetate can affect the central nervous system by inhalation causing drowsiness or dizziness. Exposure far above the OEL may result in death.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Ethyl acetate does not meet classification criteria for aquatic environmental toxicants with LC50 and EC50 of >100 mg/L.

- Ethyl acetate is biodegradable and has a minimal LC50 96 h of 220 mg/L for Pimephales promelas (fathead minnow); LC50 24 h of 560 mg/L and an EC50 48 h of 2 300 mg/L for Daphnia magna (water flea); and an EC50 72 h of 1 800 mg/L for Selenastrum (green algae).

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Section continued on the next page

ETHYL ACETATE

9620-LIQUID

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Readily Biodegradable

Other Effects

Volatile Organic Content (VOC) = 100% [902 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 1 L and under
9620-945ML
Limited Quantity



Sizes greater than 1 L
9620-3.78L

UN number: UN1173
Shipping Name: ETHYL ACETATE
Class: 3
Packing Group: II
Marine Pollutant: No



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.5 L and under
FOR REFERENCE ONLY
Limited Quantity



Max Net Qty/Pkg =
1 L

Sizes up to 5 L (passenger), 60 L (cargo)
9620-945ML, 9620-3.78L

UN number: UN1173
Shipping Name: ETHYL ACETATE
Class: 3
Packing Group: II
Marine Pollutant: No



Section continued on the next page

ETHYL ACETATE**9620-LIQUID****Sea****Refer to IMDG regulations.**

Sizes 1 L and under

9620-945ML

Limited Quantity

Sizes greater than 1 L

9620-3.78L

UN number: UN1173**Shipping Name:** ETHYL ACETATE**Class:** 3**Packing Group:** II**Marine Pollutant:** No

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

ETHYL ACETATE**9620-LIQUID****USA****Other Classifications****HMIS[®] RATING**

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains ethyl acetate (CAS# 141-78-6), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any substances known to be listed in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

ETHYL ACETATE**9620-LIQUID****Section 16: Other Information**

SDS Prepared by Michel Hachey
Date of Revision 04 March 2020
Supersedes 21 February 2018
Reason for Changes: Changes to transportation and to emergency phone numbers.

Reference

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

ETHYL ACETATE**9620-LIQUID**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.